



## DOUBLE-SIDED TAPE IN REEL AND SPOOL

**(Product code: "DST 160 APR")**

Permanent double-sided tape in cellulose TNT highly adhesive. It is especially projected for high grammage special adhesives. Suitable for gluing on plain surfaces and great with LSE plastics. High resistance to UV rays and excellent temperature range.

- ✓ **Suggested for:** Applications with automatic dispensers
- ✓ **Industries:** Paper products, Paper transformation, Corrugated machines, LSE plastics
- ✓ **Applications:** Irregular surfaces, Corrugated cardboard, Fabrics

### Technical features

<i>Support</i>	Cellulose white TNT
<i>Adhesive</i>	Acrylic
<i>Liner</i>	Glassine white paper 80 gr
<i>Formats (mm x mt)</i>	12/25x500; 9/12x1000; 12/15x3000; 20/24x2500
<i>UM</i>	M <sub>2</sub>
<i>Carrier + adhesive thickness (my)</i>	160
<i>Peel Adhesion (N/25mm)</i>	10
<i>Working temperatures (min - max)</i>	+15°/+90°

### TEST METHODS

International standards (FINAT, AFERA, PSTC, ASTM, TLMI, ISO).

### SAFETY INFORMATION

This product is not classified as dangerous for the environment or human health and it is classified as APEO free category, according to the environmental standard.

### USE AND STORAGE

The functionality and efficiency of the adhesive material is guaranteed 12 months from the date of delivery. We recommend to store it, respecting the following indications:

- Environmental Temperature from + 5 ° C to + 50 ° C
- Humidity less than 65%
- Avoid exposing the material to direct light and sources of heat
- Store the material in the original packaging and remove the packaging only before use

Before applying the adhesive tape, the surface must be clean and dry.

In case of particular processing it is advisable to evaluate the suitability of the product by means of a preliminary test.

Our technical staff is available for any support.

The producer will not be responsible for any direct, indirect or incidental loss or damage resulting from incorrect use of the product. Therefore, the user assumes all risk and liability due to improper use of this article.

**NOTE : The technical data shown in this sheet have been obtained directly from the documentation provided by the manufacturer.**

**This data may be subject to change without prior notice.**

