



# **TEAR TAPE ADHESIVE**

(Product code: "20000TEARTAPE")

Permanent single-sided tape in spools for easy opening. High shear strenght

- ✓ **Suggested for:** Paper, Polyester ( PET), Polypropylene (PPL), Polyetylene (PE)
- ✓ Industries: Flexible packaging
- ✓ Applications: Paper and plastic film bags.

## Technical features

Support	Red Polypropylene (PPL)
Adhesive	Solvent acrylic
Liner	-
Formats (mm x mt)	4x20000; 6x20000
UM	RT
Carrier + adhesive thickness (my)	60 ; 90
Peel Adhesion (N/25mm)	16
Working temperatures (min – max)	-20° / +70°

#### **TEST METHODS**

International standards (FINAT, AFERA, PSTC, ASTM, TLMI, ISO).

### **SAFETY INFORMATION**

This product is not classified as dangerous for the environment or human health and it complies with current regulations such as the REACH Regulation and the RoHS Directive.

#### **USE AND STORAGE**

The functionality and efficiency of the adhesive material is guaranteed 12 months from the date of delivery. We recommend to store it, respecting the following indications:

- Environmental Temperature from + 15 ° C to + 22 ° C
- Humidity less than 65%
- Avoid exposing the material to direct light and sources of heat
- Store the material in the original packaging and remove the packaging only before use

Before applying the adhesive tape, the surface must be clean and dry.

In case of particular processing it is advisable to evaluate the suitability of the product by means of a preliminary test.

Our technical staff is available for any support.

The productor will not be responsible for any direct, indirect or incidental loss or damage resulting from incorrect use of the product. Therefore, the user assumes all risk and liability due to improper use of this article.

NOTE: The technical data shown in this sheet have been obtained directly from the documentation provided by the manufacturer.

This data may be subject to change without prior notice.

