



DOUBLE-SIDED RED BANNER TAPE

(Product code: "BTR 160 APR")

Permanent double-sided tape, ultra clear, excellent resistance to tearing and high temperatures. Particularly suitable for punching and laser cutting thanks to its protective plastic film.

- ✓ **Suggested for:** Rubber (also synthetic and expanded), wood, laminates, expanded material, HSE and LSE plastics, Polyester-coated and crude metal.
- ✓ **Industries:** Automotive, Consumer goods, Plastic material, Marine, Furniture and furnishing, Silk screen printing
- ✓ **Applications:** Plastic material and various fabric splices; bonding plastic, metal and decorative trims; polycarbonate overlays; Banners; Sails and spinnakers.

Technical features

<i>Support</i>	Clear Polyester (PET)
<i>Adhesive</i>	Solvent acrylic
<i>Liner</i>	Filmic red
<i>Formats (mm x mt)</i>	6x50; 9x50; 12x50; 19x50; 6x200; 9x200; 12x200 19x200
<i>UM</i>	M ₂
<i>Carrier + adhesive thickness (my)</i>	205
<i>Peel Adhesion (N/25mm)</i>	17
<i>Working temperatures (min - max)</i>	NA / +100°

TEST METHODS

International standards (FINAT, AFERA, PSTC, ASTM, TLMI, ISO).

SAFETY INFORMATION

This product is not classified as dangerous for the environment or human health and it complies with current regulations such as the REACH Regulation and the RoHS Directive.

USE AND STORAGE

The functionality and efficiency of the adhesive material is guaranteed 12 months from the date of delivery. We recommend to store it, respecting the following indications:

- Environmental Temperature from + 15 ° C to + 22 ° C
- Humidity less than 65%
- Avoid exposing the material to direct light and sources of heat
- Store the material in the original packaging and remove the packaging only before use

Before applying the adhesive tape, the surface must be clean and dry.

In case of particular processing it is advisable to evaluate the suitability of the product by means of a preliminary test.

Our technical staff is available for any support.

The producer will not be responsible for any direct, indirect or incidental loss or damage resulting from incorrect use of the product. Therefore, the user assumes all risk and liability due to improper use of this article.

NOTE : The technical data shown in this sheet have been obtained directly from the documentation provided by the manufacturer.

This data may be subject to change without prior notice

